

Bradford Fireseal® Hebelstrip

Refer to product table below for applicable product codes covered by this document

Issue **B, 11/2023**

Product Type & Application

Bradford Fireseal® Hebelstrip is a non-combustible Rockwool bulk insulation product primarily used as a general-purpose insulation in industrial applications where fire and thermal properties are required.

Compliance with the New Zealand Building Code

When correctly specified and installed, this product meets or contributes to compliance with the following performance requirements of the building code:

- **B2 Durability B2.3.1(a)** – Fireseal® insulation has a well-established history of use in service.
- **C3 Fire affecting areas beyond the fire source C3.5, C3.7** - Fireseal® is non-combustible and contributes to preventing fire spread when incorporated in fire rated construction.
- **F2 Hazardous building materials F2.3.1** - Fireseal® does not emit or give rise to harmful concentrations of gas, liquid, radiation or solid particles.
- **H1 Energy Efficiency H1.3.1(a), H1.3.2E** – Fireseal® has been tested to AS/NZS 4859 to determine insulation R-values for use in accordance with Acceptable Solutions H1/AS1 and H1/AS2 and Verification Methods H1/VM1 and H1/VM2.

Specific Design or Installation Instructions

- Isolate power before installation.
- **Caution:** Electrical cables and equipment partially or completely surrounded with bulk thermal insulation may overheat and fail.
- Suitable for applications that specify non-combustible bulk insulation products - not suitable for exposed wall and ceiling lining applications that require a Group Number.
- Insulation should be installed so that forms a continuous layer and abuts or overlaps adjoining insulation other than at supporting members such as columns, studs, noggings, joists, furring channels and the like where the insulation must butt against the member.
- Suitable for interior applications where the product is protected from UV light, water and wind pressure during and after installation.

For general installation guidance refer to the product information on Bradfordinsulation.com.nz

Supplementary information - Additional installation guidance for this product can be found in AS3999.

Limitations of Use

- **IMPORTANT:** Do Not Modify This Product: Compliance with the evidence of suitability data referenced in this document is only achieved by the product or configuration listed in this PTS.
- This product is not suitable for use as an exposed internal wall or ceiling lining in applications which require a Group Number in accordance with C3.4(a).
- Unfaced Rockwool is not a water or vapour barrier and is not suitable for water or vapour control.

Conditions of Storage & Maintenance

- Store in the original packaging in a cool, dry area, away from foodstuffs. Ensure packages are adequately labelled, protected from physical damage, and sealed when not in use. Avoid packaging being stored under UV light (direct sunlight) for long periods.

Refer to the product SDS at Bradfordinsulation.com.au for more information.

Bradford Fireseal® Hebelstrip

Basis of Compliance

- Testing to AS/NZS 4859.1 across the following reports, on nominal (uncompressed) thickness -
 - AWTATA NATA Lab Report 22-002673.
- Professional Assessment, AS 1530.1 –
 - Warringtonfire Assessment Report FAS210056.
- Professional Assessment, AS/NZS 1530.3 –
 - Warringtonfire Assessment Report FAS200045.
 - Warringtonfire Assessment Report FAS210154.
- C/AS2 Acceptable Solution for Buildings other than Risk Group SH for New Zealand Building Code Clauses C1-C6 Protection from Fire First edition (Amendment 3), 2 November 2023.
- H1 Energy Efficiency, Acceptable Solution H1/AS1, Energy efficiency for all housing, and buildings up to 300 m², Fifth edition Amendment 1, 4 August 2022.
- H1 Energy Efficiency, Acceptable Solution H1/AS2, Energy efficiency for buildings greater than 300 m², First edition Amendment 1, 4 August 2022.
- H1 Energy Efficiency, Verification Method H1/VM1, Energy efficiency for all housing, and buildings up to 300 m², Fifth edition Amendment 1, 4 August 2022.
- H1 Energy Efficiency, Verification Method H1/VM2, Energy efficiency for all housing, and buildings greater than 300 m², First edition Amendment 1, 4 August 2022.
- Bradford SDS FBS-1 Rockwool Insulation Products, 1st November 2024.

Applicable Product Codes

R-VALUE (m²K/W)	THICKNESS (mm)	NOMINAL LENGTH (m)	NOMINAL WIDTH (mm)	PIECES PER PACK	m² PER PACK	PRODUCT CODE
Fireseal® Hebelstrip						
R0.39	13	0.75	225	15	2.5	181341

Material R-values are determined in accordance with AS/NZS 4859.1 at 23°C and apply to the product installed at nominal thickness.

Additional Product Data

Nominal Density		Fireseal® Hebelstrip - 110kg/m³
Fire Hazard Properties	When assessed in accordance with AS/NZS 1530.3	• Ignitability: 0 • Spread of flame: 0 • Heat Evolved: 0 • Smoke Developed: 1
Non-Combustibility	When assessed to AS 1530.1	Non - Combustible

Bradford NZ, 14 The Furlong, Takanini, Auckland For further technical advice call 0800 277 123/ visit bradfordinsulation.co.nz/ email bradford@csr.co.nz

Bradford NZ is a business division of CSR Building Products (NZ) Limited (NZBN 9429040750194)

CSR Bradford is a business division of CSR Building Products Limited (ABN 55 008 831 356)

The contents of this brochure are copyright protected and may not be reproduced in any form without prior written consent of CSR Bradford. Recommendations and advice regarding the use of the products described in this brochure are to be taken as a guide only, and are given without liability on the part of the company or its employees. We reserve the right to change product specifications without prior notification. Please refer to the CSR Bradford website for the latest revision of this document. The purchaser should independently determine the suitability of the product for the intended use and application.

Bradford Fireseal[®] Hebelstrip

Other Accreditation



FBS-1 Rockwool - The fibre component of these products is listed by Safe Work Australia as Man-made Vitreous Fibre (Rockwool) of low bio persistence as specified under Note Q in the Australian Hazardous Substances Information System and in the Australian Approved Criteria documentation. In accordance with EU ATP 31 (2009) these fibres are not classified as an irritant, or as carcinogenic.
Refer to the product SDS at Bradfordinsulation.com.au for more information.