

Bradford Gold® & Gold Hi-Performance

Refer to product table below for applicable product codes covered by this document

Issue **F, 1/2025**

Product Type & Application

Bradford Gold® and Gold Hi-Performance (HP) are Glasswool thermal insulation products. They are for use in external walls and ceilings to reduce heat transfer through the building envelope.

Compliance with the New Zealand Building Code

When correctly specified and installed, this product meets or contributes to compliance with the following performance requirements of the building code:

- **B2 Durability** B2.3.1(a) – Glasswool insulation has a well-established history of use in service.
- **E3 Internal Moisture** E3.3.1 - Bradford Gold® and Gold Hi-Performance (HP) products listed in this PTS exceed R1.5 as in Acceptable Solution E3/AS1 and contribute to compliance with E3.3.1
- **F2 Hazardous building materials** F2.3.1 - Bradford Gold® and Gold Hi-Performance (HP) do not emit or give rise to harmful concentrations of gas, liquid, radiation or solid particles.
- **H1 Energy Efficiency** H1.3.1(a), H1.3.2E - Bradford Gold® and Gold Hi-Performance (HP) have been tested to AS/NZS 4859.1 to determine insulation R-values for use in accordance with Acceptable Solutions H1/AS1 and H1/AS2 and Verification Methods H1/VM1 and H1/VM2.

Limitations of Use

- **IMPORTANT:** Do Not Modify This Product: Compliance with the evidence of suitability data referenced in this document is only achieved by the product or configuration listed in this PTS.
- **IMPORTANT:** R2.6, R2.8, and R4.0(HP) Wall Batts are high-density products that will not compress during installation and must be installed in a cavity of the correct size, with no obstructions. If installed in a cavity smaller than the product's nominal thickness, there is a risk of deformation or detachment of rigid wall lining materials.
- This product is not suitable for use as an exposed internal wall or ceiling lining in applications which require a Group Number in accordance with NZBC clause C3.4(c).
- Unfaced Glasswool is not a water or vapour barrier and is not suitable for water or vapour control.
- Maximum service temperature is 150°C for unfaced Glasswool.
- Check the plasterboard, ceiling tile or ceiling grid manufacturer's weight limitations prior to increasing the recommended R-Values or densities to ensure the structure can support the additional weight of the batts.

Limitations of Use cont.

- This product is not subject to any warning or ban declared by MBIE under section 26 of the Building Act 2004.

Specific Design or Installation Instructions

- Isolate power before installation.
- **Caution:** Electrical cables and equipment partially or completely surrounded with bulk thermal insulation may overheat and fail. In new build construction with electrical wiring in accordance with AS/NZS 3000: 2018 or later, wiring may be partially or completely surrounded for up to 400mm. If more than 400mm is surrounded, or for wiring pre AS/NZS 3000:2018, seek advice from a licenced electrician. Refer to legislation and referenced standards for full details or seek advice from an electrician if in doubt.
- **IMPORTANT:** R2.6, R2.8, and R4.0(HP) Wall Batts are high-density products that will not compress during installation and must be installed in a cavity of the correct size, with no obstructions. If installed in a cavity smaller than the product's nominal thickness, there is a risk of deformation or detachment of rigid wall lining materials.
- Insulation should be installed so that it forms a continuous layer and abuts or overlaps adjoining insulation other than at supporting members such as columns, studs, noggings, joists, furring channels and the like where the insulation must butt against the member.
- It should be installed at nominal thickness, except where it crosses structures, services and fittings.
- Ceiling perimeter batts may be required to achieve compliance depending upon roof and exterior wall design.
- Suitable for interior applications where the product is protected from direct UV light, water and wind pressure during and after installation.

For general installation guidance refer to the product installation guide at Bradfordinsulation.co.nz

Product installation information - Additional installation guidance for this product can be found in NZS 4246:2016.

Conditions of Storage, Use & Maintenance

Store in the original packaging in a cool, dry area, away from foodstuffs. Ensure packages are adequately labelled, protected from physical damage, and sealed when not in use. Avoid packaging being stored under UV light (direct sunlight) for long periods.

Refer to the product SDS at Bradfordinsulation.com.au for more information.

Bradford Gold® & Gold Hi-Performance

Basis of Compliance

- BRANZ Appraisal 301.
- Testing to AS/NZS 4859.1 across the following reports-
 - BRANZ Report DI11505-002-02
 - BRANZ Report DI12309-001-02
 - BRANZ Report DI13245-001-02
 - BRANZ Report DI16104-01
 - BRANZ Report DI16104-03
 - BRANZ Report DI16104-11
 - BRANZ Report DI16104-15
 - BRANZ Report DI16104-17
 - BRANZ Report DI16104-18
 - BRANZ Report TP13869-003-01
 - BRANZ Report TP13869-004-01
 - BRANZ Report TP13869-005-01
 - BRANZ Report TP13869-011
 - BRANZ Report TP13869-012
 - BRANZ Report TP13869-016
 - BRANZ Report TP13869-017
- Acceptable Solutions and Verification Methods for New Zealand Building Code Clause E3 Internal Moisture Second edition Amendment 7, 5 November 2020.
- H1 Energy Efficiency, Acceptable Solution H1/AS1, Energy efficiency for all housing, and buildings up to 300m², Fifth edition Amendment 1, 4 August 2022.
- H1 Energy Efficiency, Acceptable Solution H1/AS2, Energy efficiency for buildings greater than 300m², First edition Amendment 1, 4 August 2022.
- H1 Energy Efficiency, Verification Method H1/VM1, Energy efficiency for all housing, and buildings up to 300m², Fifth edition Amendment 1, 4 August 2022.
- H1 Energy Efficiency, Verification Method H1/VM2, Energy efficiency for all housing, and buildings greater than 300m², First edition Amendment 1, 4 August 2022.
- Bradford SDS CSR-SHE-Glasswool Issued 24th September 2024.

Bradford NZ, 14 The Furlong, Takanani, Auckland For further technical advice call 0800 277 123/ visit bradfordinsulation.co.nz/ email bradford@csr.co.nz

Bradford NZ is a business division of CSR Building Products (NZ) Limited (NZBN 9429040750194)

CSR Bradford is a business division of CSR Building Products Limited (ABN 55 008 831 356). Manufactured by CSR Building Products Limited.

The contents of this brochure are copyright protected and may not be reproduced in any form without prior written consent of CSR Bradford. Recommendations and advice regarding the use of the products described in this brochure are to be taken as a guide only, and are given without liability on the part of the company or its employees. We reserve the right to change product specifications without prior notification. Please refer to the CSR Bradford website for the latest revision of this document. The purchaser should independently determine the suitability of the product for the intended use and application.



Bradford Gold® & Gold Hi-Performance

Applicable Product Codes – Ceiling Products

| R-VALUE (m ² K/W) | THICKNESS (mm) | STANDARD SIZE (mm) | PIECES PER PACK | m ² PER PACK | PRODUCT CODE |
|------------------------------|----------------|--------------------|-----------------|-------------------------|--------------|
| R1.8 | 90 | 1160 x 430 | 22 | 11.0 | 480025 |
| R1.8 | 95 | 1160 x 430 | 24 | 11.9 | 38199 |
| R2.9 | 145 | 1160 x 430 | 20 | 10.0 | 468022 |
| R3.3 | 165 | 1160 x 430 | 16 | 8.0 | 468023 |
| R3.6 | 185 | 1160 x 430 | 16 | 8.0 | 474662 |
| R4.0 | 215 | 1160 x 430 | 12 | 6.0 | 84834 |
| R5.2 (HP) | 240 | 1160 x 430 | 8 | 4.0 | 474661 |
| R6.0 (HP) | 260 | 1160 x 430 | 6 | 3.0 | 79717 |
| R6.3 (HP) | 260 | 1160 x 430 | 6 | 3.0 | 480048 |
| R7.3 (HP) | 290 | 1160 x 430 | 4 | 2.0 | 480049 |
| R7.3 (HP) | 290 | 1160 x 450 | 4 | 2.1 | 483801 |

Applicable Product Codes – Wall Products

| R-VALUE [m ² K/W] | THICKNESS [mm] | STANDARD SIZE [mm] | PIECES PER PACK | m ² PER PACK | PRODUCT CODE |
|------------------------------|----------------|--------------------|-----------------|-------------------------|--------------|
| R1.8 | 90 | 1160 x 580 | 22 | 14.8 | 84836 |
| R2.2 | 90 | 1160 x 580 | 16 | 10.8 | 84838 |
| R2.4 | 90 | 1160 x 580 | 10 | 6.7 | 104734 |
| R2.6 | 90 | 1160 x 580 | 8 | 5.4 | 86961 |
| R2.8 | 90 | 1160 x 580 | 5 | 3.4 | 118544 |
| R3.5 | 140 | 1160 x 580 | 10 | 6.7 | 126862 |
| R4.0 (HP) | 140 | 1160 x 580 | 5 | 3.4 | 125449 |

Additional Product Data

| | | |
|--|--|---|
| Maximum Service Temperature | | 150°C (suitable where a long-term surface operating temperature ≥90°C is required for insulation around heat generating equipment.) |
| Sample Specification – Wall Products | The insulation material shall be Bradford Gold® or Bradford Gold® Hi-Performance having a material R-Value; Rm...(specify R-Value) @ XXmm... (specify thickness). | |
| Sample Specification – Ceiling Products | The insulation material shall be Bradford Gold® or Bradford Gold® Hi-Performance Ceiling Batts R ___ m ² K/W (specify type) as manufactured by Bradford Insulation. | |

Bradford NZ, 14 The Furlong, Takanini, Auckland For further technical advice call 0800 277 123/ visit bradfordinsulation.co.nz/ email bradford@csr.co.nz

Bradford NZ is a business division of CSR Building Products (NZ) Limited (NZBN 9429040750194)

CSR Bradford is a business division of CSR Building Products Limited (ABN 55 008 831 356). Manufactured by CSR Building Products Limited.

The contents of this brochure are copyright protected and may not be reproduced in any form without prior written consent of CSR Bradford. Recommendations and advice regarding the use of the products described in this brochure are to be taken as a guide only, and are given without liability on the part of the company or its employees. We reserve the right to change product specifications without prior notification. Please refer to the CSR Bradford website for the latest revision of this document. The purchaser should independently determine the suitability of the product for the intended use and application.



Bradford Gold® & Gold Hi-Performance

Other Accreditation



FBS-1 Glasswool - The fibre component of these products is listed by Safe Work Australia as Man-made Vitreous Fibre (Glasswool) of low bio persistence as specified under Note Q in the Australian Hazardous Substances Information System and in the Australian Approved Criteria documentation. In accordance with EU ATP 31 (2009) these fibres are not classified as an irritant, or as carcinogenic.
Refer to the product SDS at Bradfordinsulation.com.au for more information.



National Asthma Council Sensitive Choice

Bradford NZ, 14 The Furlong, Takanini, Auckland For further technical advice call 0800 277 123/ visit bradfordinsulation.co.nz/ email bradford@csr.co.nz

Bradford NZ is a business division of CSR Building Products (NZ) Limited (NZBN 9429040750194)

CSR Bradford is a business division of CSR Building Products Limited (ABN 55 008 831 356). Manufactured by CSR Building Products Limited.

The contents of this brochure are copyright protected and may not be reproduced in any form without prior written consent of CSR Bradford. Recommendations and advice regarding the use of the products described in this brochure are to be taken as a guide only, and are given without liability on the part of the company or its employees. We reserve the right to change product specifications without prior notification. Please refer to the CSR Bradford website for the latest revision of this document. The purchaser should independently determine the suitability of the product for the intended use and application.

